

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**




Fig 1






FIG 2.






Fig 3




FIG-4




FIG 5





FIG. 6






Fig 10




Fig 11

BZ5 - Beam Forming Mode

DIRECTIONALITY	
—	500Hz, DI = 6.6
—	1000Hz, DI = 11.1
—	2000Hz, DI = 8.5
—	4000Hz, DI = 10.5




Fig 12

BZ-5 In-Situ Right Ear Polar Response




Fig 13

Second Order - Beam Forming Mode

DIRECTIONALITY	
—	500Hz, DI = 8.9
—	1000Hz, DI = 9.3
—	2000Hz, DI = 11.5
—	4000Hz, DI = 11.5




Fig 14

SHAW DATA - Azimuthal Interaural Difference

Azimuth Angle (Deg.)	IAD @ 500 Hz (dB)	IAD @ 1 kHz (dB)	IAD @ 2 kHz (dB)	IAD @ 4 kHz (dB)
0	0	0	0	0
10	1.4	2.3	1.8	3
20	2.7	4.5	3.5	6.4
30	4	6.8	5.2	9.2
40	5.3	8.5	6.8	12
50	5.9	9.5	8.35	14.1
60	6	9.2	9.8	15.2
70	5.8	8.2	10.3	15
80	5.75	7.4	9.5	14
90	5.6	7	8.6	12.8
100	5.7	7.4	9.5	12.05
110	5.85	8.5	10.3	11.4
120	6	9.3	9.8	9.8
130	5.9	9.8	8.35	7.7
140	5.5	9	6.8	6
150	4.5	7.35	5.2	4.2
160	3.1	4.9	3.5	2.7
170	1.7	2.5	1.8	1.3
180	0	0	0	0

Fig 15

BEAMFORMER - Azimuthal Dependence of Electrical Phase Difference

Azimuth Angle (Deg.)	BF Phase @ 500 Hz (Deg.)	BF Phase @ 1 kHz (Deg.)	BF Phase @ 2 kHz (Deg.)	BF Phase @ 4 kHz (Deg.)
0	0	0	0	0
5				
10				
15				180
20				
25				
30			180	360
35				
40				
45				540
50				
55				
60		180	360	720
65				
70				
75				
80				
85				
90	<180			

Fig 17

INTERAURAL DIFFERENCE




Fig 16

Using the 1-kHz Pattern As the Desired Reference Polar Pattern

FREQ.	ACTION	IAD SLOPE (dB/ADeg)	PHASE SLOPE (EDeg/ADeg)	PHASE RATE (EDeg/dB)	CORRECTION (EDeg/dB)
At 500 Hz	Double the phase rate	18 dB / 70 deg. = 0.22857	90 / 60 = 1.5	6.563	6.563
At 1 kHz	Do Nothing	16 dB / 120 deg. = 0.13333	180 / 60 = 3	22.500	0
At 2 kHz	Halve the phase rate	10 dB / 60 deg. = 0.16667	180 / 30 = 6	36.000	-18
At 4 kHz	Quarter the phase rate	12 dB / 40 deg. = 0.30000	180 / 15 = 12	40.000	-30

Fig 18

CONTROL SURFACE - Electr. Deg.

IAD (dB)	FREQ (kHz)							
	0.5	1	2	4	8	16	32	64
0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1	6.56	3.28	0.00	-9.00	-18.00	-24.00	-30.00	-36.00
2	13.13	6.56	0.00	-18.00	-36.00	-48.00	-60.00	-72.00
3	19.69	9.84	0.00	-27.00	-54.00	-72.00	-90.00	-108.00
4	26.25	13.13	0.00	-36.00	-72.00	-96.00	-120.00	-144.00
5	32.82	16.41	0.00	-45.00	-90.00	-120.00	-150.00	-180.00
6	39.38	19.69	0.00	-54.00	-108.00	-144.00	-180.00	-210.00
7	45.94	22.97	0.00	-63.00	-126.00	-168.00	-210.00	-240.00
8	52.50	26.25	0.00	-72.00	-144.00	-192.00	-240.00	-270.00
9	59.07	29.53	0.00	-81.00	-162.00	-216.00	-270.00	-300.00
10	65.63	32.82	0.00	-90.00	-180.00	-240.00	-300.00	-360.00
11	72.19	36.10	0.00	-99.00	-198.00	-264.00	-330.00	-390.00
12	78.76	39.38	0.00	-108.00	-216.00	-288.00	-360.00	-420.00
13	85.32	42.66	0.00	-117.00	-234.00	-312.00	-390.00	-450.00
14	91.88	45.94	0.00	-126.00	-252.00	-336.00	-420.00	-480.00
15	98.45	49.22	0.00	-135.00	-270.00	-360.00	-450.00	-510.00
16	105.01	52.50	0.00	-144.00	-288.00	-384.00	-480.00	-540.00
17	111.57	55.79	0.00	-153.00	-306.00	-408.00	-510.00	-570.00
18	118.13	59.07	0.00	-162.00	-324.00	-432.00	-540.00	-600.00
19	124.70	62.35	0.00	-171.00	-342.00	-456.00	-570.00	-630.00
20	131.26	65.63	0.00	-180.00	-360.00	-480.00	-600.00	-660.00

Fig 19

REQUIRED ELECTRICAL PHASE SHIFT
(As a Function of Frequency and Interaural Difference)




Fig 20

CORRECTION SLOPE




Fig 21




Fig 22




Fig 23

BZ5/Phase Corrected - Beam Forming Mode (Calculated)

<u>DIRECTIONALITY</u>	
—	500Hz, DI = 9.4
—	1000Hz, DI = 11.1
—	2000Hz, DI = 9.7
—	4000Hz, DI = 12.4




Fig 24